

## Wetta 8036 Plastic Impact Sprinkler, 3/4" Male

The W8036 impact sprinkler comes in a wide range of brass and plastic nozzles and is perfect for solid set irrigation in agricultural crops and nurseries.

### Wetta 8036 Features:

- Operating pressure 250 Kpa - 450 Kpa
- High distribution uniformity with spacing up to 18m x 18m
- 25 degree front and rear nozzles
- Integrated vane straighteners
- High quality plastic - resistant to corrosion and radiation
- Brass nozzles (also available with plastic nozzles)

### 8036 Performance Table



#### Single Nozzle

Nozzle mm	P Kpa	Q L/m	Diameter m
4.0	300	17.1	27
	350	18.8	30
	400	20.16	30
4.4	300	20.6	30
	350	22.6	31
	400	24.1	32
4.8	300	25.0	31
	350	27.1	32
	400	28.6	33
5.2	300	29.5	31
	350	32.1	33
	400	34.1	34
5.6	300	29.6	28
	350	37.1	29
	400	39.3	30

#### Dual nozzle

Nozzle mm	P Kpa	Q L/m	D m	Precipitation Rate mm - Spacing (m)				
				12 x 12	12 x 15	15 x 15	5 x 18	18 x 18
3.5 x 2.4	300	20.4	26	8.5	6.8	5.4	3.7	3.8
	350	20.0	28	9.2	7.4	5.9	4.0	4.1
	400	23.6	28	9.8	7.9	6.3	4.3	4.4
4.0 x 2.4	300	23.7	29	9.9	7.9	6.3	4.3	4.4
	350	25.6	30	10.7	8.6	6.8	4.7	4.8
	400	27.4	30	11.4	9.1	7.3	5.0	5.1
4.5 x 2.4	300	36.3	30	15.1	12.1	9.7	6.6	6.7
	350	39.2	31	16.3	13.1	10.5	7.1	7.3
	400	41.95	32	17.5	14.0	11.2	7.6	7.8
5.0 x 3.2	300	36.8	30	15.3	12.2	9.8	8.2	6.8
	350	40.0	32	16.6	13.3	10.6	8.9	7.4
	400	43.1	32	18.0	14.4	11.5	9.6	7.8
5.5 x 3.2	300	41.0	33	17.0	13.6	10.9	9.1	7.6
	350	44.5	35	18.5	14.8	11.8	9.9	8.2
	400	47.6	36	19.8	15.9	12.7	10.6	8.8