

PRS8030 Pop-up Sprinkler

Wetta PRS8030 Features:

- 210 KPa pressure regulated
- Adjustable Nozzles
- 1/2" female inlet
- 15.5cm height
- Large water droplets to withstand light winds
- Adjustable from 0° 360°
- 1.3m radius adjustable nozzles available



		2.4 m Radius Adjustable from 0° to 260° Trajectory: 0° color code: Brown ●				3.0 m Radius Adjustable from 0° to 360° Trajectory: 15° color code: Red ●				3.7 m Radius Adjustable from 0° to 360° Trajectory: 28° color code: Green ●				4.6 m Radius Adjustable from 0° to 360° Trajectory: 28° color code: Black ●				5.2 m Radius Adjustable from 0° to 360° Trajectory: 28° color code: Grey ●			
Arc	Pressure	Radius	Flow	Precip mm/hr		Radius	Flow	Precip mm/hr		Radius	Flow	Precip mm/hr		Radius	Flow	Precip mm/hr		Radius	Flow	Precip mm/hr	
	Kpa	m	L/m	■	▲	m	L/m	■	▲	m	L/min	■	▲	m	L/min	■	▲	m	L/min	■	▲
45°	100	1.7	0.37	62	72	2.1	0.63	68	79	2.7	0.81	53	61	3.4	1.19	50	57	4.7	1.54	33	39
	150	2.1	0.47	51	59	2.4	0.79	66	76	3.2	1.01	47	55	3.9	1.49	47	54	4.9	1.93	38	44
	200	2.4	0.55	46	53	3.0	0.92	49	57	3.7	1.18	42	48	4.6	1.75	40	46	5.2	2.26	40	46
	210	2.7	0.56	37	43	3.3	0.95	42	48	4.0	1.22	36	42	4.9	1.80	36	41	5.5	2.32	37	42
90°	100	1.7	0.75	62	72	2.1	1.26	68	79	2.7	1.62	53	61	3.4	2.39	50	57	4.7	3.08	33	39
	150	2.1	0.93	51	59	2.4	1.57	66	76	3.2	2.02	47	55	3.9	2.89	47	54	4.9	3.85	38	44
	200	2.4	1.09	46	53	3.0	1.84	49	57	3.7	2.37	42	48	4.6	3.50	40	46	5.2	4.51	40	46
	210	2.7	1.12	37	43	3.3	1.89	42	48	4.0	2.43	36	42	4.9	3.59	36	41	5.4	4.63	37	42
120°	100	1.7	1.00	62	72	2.1	1.68	68	79	2.7	2.16	53	61	3.4	3.18	50	57	4.7	4.11	33	39
	150	2.1	1.24	51	59	2.4	2.10	66	76	3.2	2.70	47	55	3.9	3.98	47	54	4.9	5.13	38	44
	200	2.4	1.46	46	53	3.0	2.46	49	57	3.7	3.16	42	48	4.6	4.66	40	46	5.2	6.01	40	46
	210	2.7	1.50	37	43	3.3	2.52	42	48	4.0	3.24	36	42	4.9	4.79	36	41	5.5	6.18	37	42
180°	100	1.7	1.49	62	72	2.1	1.68	68	79	2.7	3.23	53	61	3.4	4.77	50	57	4.7	6.16	33	39
	150	2.1	1.87	51	59	2.4	2.10	66	76	3.2	4.04	47	55	3.9	5.97	47	54	4.9	7.70	38	44
	200	2.4	2.19	46	53	3.0	2.46	49	57	3.7	4.74	42	48	4.6	6.99	40	46	5.2	9.02	40	46
	210	2.7	2.25	37	43	3.3	2.52	42	48	4.0	4.86	36	42	4.9	7.18	36	41	5.5	9.27	37	42
240°	100	1.7	1.99	62	72	2.1	2.52	68	79	2.7	4.31	53	61	3.4	6.37	50	57	4.7	8.21	33	39
	150	2.1	2.49	51	59	2.4	3.14	66	76	3.2	5.39	47	55	3.9	7.96	47	54	4.9	10.27	38	44
	200	2.4	2.92	46	53	3.0	3.68	49	57	3.7	6.31	42	48	4.6	9.32	40	46	5.2	12.03	40	46
	210	2.7	2.99	37	43	3.3	3.78	42	48	4.0	6.49	36	42	4.9	9.57	36	41	5.5	12.35	37	42
270°	100	1.7	2.24	62	72	2.1	3.77	68	79	2.7	4.85	53	61	3.4	7.16	50	57	4.7	9.24	33	39
	150	2.1	2.8	51	59	2.4	4.72	66	76	3.2	6.06	47	55	3.9	8.95	47	54	4.9	11.55	38	44
	200	2.4	3.28	46	53	3.0	5.52	49	57	3.7	7.10	42	48	4.6	10.49	40	46	5.2	13.53	40	46
	210	2.7	3.37	37	43	3.3	5.68	42	48	4.0	7.30	36	42	4.9	10.77	36	41	5.5	13.90	37	42
360°	100	1.7	2.9	62	72	2.1	5.03	68	79	2.7	6.47	53	61	3.4	9.55	50	57	4.7	12.32	33	39
	150	2.1	3.73	51	59	2.4	6.29	66	76	3.2	8.09	47	55	3.9	11.94	47	54	4.9	15.40	38	44
	200	2.4	4.37	46	53	3.0	7.37	49	57	3.7	9.47	42	48	4.6	13.98	40	46	5.2	18.04	40	46
	210	2.7	4.49	37	43	3.3	7.57	42	48	4.0	9.73	36	42	4.9	14.36	36	41	5.5	18.53	37	42